

GLAZING OPTIONS	STYLE	SHGC	U-VALUE	U-FACTOR	ER	VT	CANADA ENERGY STAR ZONE
Cl-Arg-180	●	0.43	0.26	1.45	33	0.49	1,2
Cl-Arg-180, Div under 1"	●	0.39	0.26	1.48	30	0.44	1,2
180-Arg-Cl	●	0.40	0.26	1.45	31	0.49	1,2
180-Arg-Cl, Div under 1"	●	0.37	0.26	1.48	29	0.44	1,2
180-Arg-i89	●	0.39	0.22	1.27	35	0.48	1,2,3
180-Arg-i89, Div under 1"	●	0.35	0.22	1.27	32	0.43	1,2
Lami-Arg-180	●●	0.39	0.26	1.45	31	0.48	1,2
180-Arg-Cl-Arg-180	●●●	0.35	0.19	1.07	37	0.43	1,2,3
180-Arg-Cl-Arg-180, Div under 1"	●●●	0.32	0.19	1.09	34	0.39	1,2,3
180-Arg/Kry-Cl-Arg/Kry-180	●●●	0.35	0.18	1.04	37	0.43	1,2,3
180-Arg/Kry-Cl-Arg/Kry-180 Div under 1"	●●●	0.32	0.19	1.08	35	0.39	1,2,3
180-Kry-Cl-Kry-180	●●●	0.35	0.17	0.96	39	0.43	1,2,3
180-Kry-Cl-Kry-180, Div under 1"	●●●	0.32	0.18	1.00	36	0.39	1,2,3
272-Arg-Cl-Arg-272	●●●	0.22	0.18	1.05	30	0.35	1,2,3
272-Arg-Cl-Arg-272, Div under 1"	●●●	0.20	0.19	1.07	28	0.32	1,2,3
272-Arg/Kry-Cl-Arg/Kry-272	●●●	0.22	0.18	1.02	30	0.35	1,2,3
272-Arg/Kry-Cl-Arg/Kry-272, Div under 1"	●●●	0.20	0.18	1.05	28	0.32	1,2,3
272-Kry-Cl-Kry-272	●●●	0.22	0.16	0.93	32	0.35	1,2,3
272-Kry-Cl-Kry-272 Div	●●●	0.20	0.17	0.97	30	0.32	1,2,3

Structural Ratings

AAMA/WDMA/CSA 101/I.S.2/A440-11 and A440S1-14
 Size Tested: 710 x 1650mm (28" x 65")
 R-PG55
 Positive Design Pressure = +2640 Pa (+55 psf)
 Negative Design Pressure = -2640 Pa (-55 psf)
 Water Test Pressure: 720Pa
 Canadian Air Infiltration/Exfiltration: A3

Double Pane Glass ●
 Tri-pane Laminated Glass ●●
 Triple Pane Glass ●●●

