

GLAZING OPTIONS	STYLE	SHGC	U-VALUE	U-FACTOR	ER	VT	CANADA ENERGY STAR ZONE
Cl-Arg-180	●	0.43	0.26	1.46	33	0.49	1,2
Cl-Arg-180, Div under 1"	●	0.39	0.26	1.48	30	0.44	1,2
180-Arg-Cl	●	0.40	0.26	1.46	31	0.49	1,2
180-Arg-Cl, Div under 1"	●	0.37	0.26	1.48	29	0.44	1,2
180-Arg-i89	●	0.47	0.22	1.25	40	0.58	1,2,3
180-Arg-i89, Div under 1"	●	0.42	0.22	1.25	37	0.52	1,2,3
Lami-Arg-180	●●	0.39	0.26	1.46	31	0.48	1,2
180-Arg-Cl-Arg-180	●●●	0.35	0.20	1.15	35	0.43	1,2,3
180-Arg-Cl-Arg-180, Div under 1"	●●●	0.35	0.21	1.15	35	0.39	1,2,3
180-Arg/Kry-Cl-Arg/Kry-180	●●●	0.35	0.18	1.05	37	0.43	1,2,3
180-Arg/Kry-Cl-Arg/Kry-180 Div under 1"	●●●	0.32	0.19	1.08	35	0.39	1,2,3
180-Kry-Cl-Kry-180	●●●	0.35	0.17	0.96	39	0.43	1,2,3
180-Kry-Cl-Kry-180, Div under 1"	●●●	0.32	0.17	0.99	37	0.39	1,2,3
272-Arg-Cl-Arg-272	●●●	0.22	0.20	1.13	28	0.35	1,2,3
272-Arg-Cl-Arg-272, Div under 1"	●●●	0.20	0.20	1.16	26	0.32	1,2,3
272-Arg/Kry-Cl-Arg/Kry-272	●●●	0.22	0.18	1.02	31	0.35	1,2,3
272-Arg/Kry-Cl-Arg/Kry-272, Div under 1"	●●●	0.20	0.19	1.05	29	0.32	1,2,3
272-Kry-Cl-Kry-272	●●●	0.22	0.16	0.94	32	0.35	1,2,3
272-Kry-Cl-Kry-272 Div	●●●	0.20	0.17	0.97	31	0.32	1,2,3

Structural Ratings

AAMA/WDMA/CSA 101/I.S.2/A440-11 and A440S1-14
 Size Tested: 1220x 1015mm (48" x 40")
 R-PG55
 Positive Design Pressure = +2640 Pa (+55 psf)
 Negative Design Pressure = -2640 Pa (-55 psf)
 Water Test Pressure: 720Pa
 Canadian Air Infiltration/Exfiltration: A3

Double Pane Glass ●
 Tri-pane Laminated Glass ●●
 Triple Pane Glass ●●●



THERMAL PERFORMANCE RATINGS

WC-125 AWNING