

GLAZING OPTIONS	STYLE	SHGC	U-VALUE	U-FACTOR	ER	VT	CANADA ENERGY STAR ZONE
Cl-Arg-180	●	0.54	0.29	1.63	34	0.61	1,2,3
Cl-Arg-180, Div under 1"	●	0.48	0.29	1.63	31	0.55	1,2
180-Arg-Cl	●	0.50	0.28	1.61	32	0.61	1,2
180-Arg-Cl, Div under 1"	●	0.45	0.28	1.61	30	0.55	1,2
180-Arg-i89	●	0.49	0.24	1.38	37	0.60	1,2,3
180-Arg-i89, Div under 1"	●	0.44	0.24	1.38	34	0.53	1,2,3
Lami-Arg-180	●●	0.48	0.30	1.69	30	0.60	1,2

Structural Ratings

AAMA/WDMA/CSA 101/1.S.2/A440-08
 and A44051-14
 Size Tested: 1600 x 1100 mm (63" x
 43")
 R-PG25
 Positive Design Pressure = +1920 Pa
 (+40 psf)
 Negative Design Pressure = -1920 Pa (-
 40 psf)
 Water Test Pressure: 180Pa
 Canadian Air Infiltration/Exfiltration: A2

Double Pane Glass ●
 Tri-pane Laminated Glass ●●
 Triple Pane Glass ●●●



WC-200 SINGLE SLIDER TILT

THERMAL PERFORMANCE RATINGS