

GLAZING OPTIONS	STYLE	SHGC	U-VALUE	U-FACTOR	ER	VT	CANADA ENERGY STAR ZONE
CI-Arg-180	●	0.53	0.28	1.61	34	0.61	1,2,3
CI-Arg-180, Div under 1"	●	0.48	0.28	1.61	31	0.55	1,2
180-Arg-CI	●	0.50	0.28	1.61	32	0.61	1,2
180-Arg-CI, Div under 1"	●	0.45	0.28	1.61	29	0.55	1,2
180-Arg-i89	●	0.49	0.24	1.37	37	0.60	1,2,3
180-Arg-i89, Div under 1"	●	0.44	0.24	1.37	34	0.53	1,2,3
Lami-Arg-180	●●	0.48	0.29	1.67	30	0.60	1,2

### Structural Ratings

AAMA/WDMA/CSA 101/1.S.2/A440-08 and A440S1-14  
 Size Tested: 1100 x 1600 mm (43" x 63")  
 R-PG35  
 Positive Design Pressure = +1920 Pa (+40 psf)  
 Negative Design Pressure = -1920 Pa (-40 psf)  
 Water Test Pressure: 260Pa  
 Canadian Air Infiltration/Exfiltration: A2

Double Pane Glass ●  
 Tri-pane Laminated Glass ●●  
 Triple Pane Glass ●●●



THERMAL PERFORMANCE RATINGS

# WC-201 SINGLE HUNG TILT