

GLAZING OPTIONS	STYLE	SHGC	U-VALUE	U-FACTOR	ER	VT	CANADA ENERGY STAR ZONE
Cl-Arg-180	●	0.44	0.26	1.48	33	0.50	1,2
Cl-Arg-180, Div under 1"	●	0.40	0.26	1.49	30	0.45	1,2
180-Arg-Cl	●	0.41	0.26	1.46	32	0.50	1,2
180-Arg-Cl, Div under 1"	●	0.38	0.26	1.49	29	0.45	1,2
180-Arg-i89	●	0.40	0.22	1.27	35	0.49	1,2,3
180-Arg-i89, Div under 1"	●	0.36	0.22	1.27	33	0.44	1,2
272-Arg-Cl-Arg-272	●	0.23	0.20	1.14	28	0.36	1,2,3
Lami-Arg-180	●●	0.40	0.26	1.48	30	0.49	1,2
180-Arg-Cl-Arg-180	●●●	0.36	0.19	1.08	37	0.44	1,2,3
180-Arg-Cl-Arg-180, Div under 1"	●●●	0.33	0.20	1.11	34	0.40	1,2,3
180-ArgKry-Cl-ArgKry-180	●●●	0.36	0.19	1.06	37	0.44	1,2,3
180-ArgKry-Cl-ArgKry-180, Div under 1"	●●●	0.33	0.19	1.09	35	0.40	1,2,3
180-Kry-Cl-Kry-180	●●●	0.36	0.17	0.97	39	0.44	1,2,3
180-Kry-Cl-Kry-180, Div under 1"	●●●	0.33	0.18	1.01	37	0.40	1,2,3
272-Arg-Cl-Arg-272, Div under 1"	●●●	0.21	0.21	1.17	26	0.33	1,2,3
272-ArgKry-Cl-ArgKry-272	●●●	0.23	0.18	1.03	30	0.36	1,2,3
272-ArgKry-Cl-ArgKry-272, Div under 1"	●●●	0.21	0.19	1.07	28	0.33	1,2,3
272-Kry-Cl-Kry-272	●●●	0.23	0.17	0.94	32	0.36	1,2,3
272-Kry-Cl-Kry-272, Div under 1"	●●●	0.21	0.17	0.98	30	0.33	1,2,3

Structural Ratings

AAMA/WDMA/CSA 101/1.2/A440-11 and A440S1-14
 Size Tested: 710 x 1650mm (28" x 65")
 R-PG55
 Positive Design Pressure = +2640 Pa (+55 psf)
 Negative Design Pressure = -2640 Pa (-55 psf)
 Water Test Pressure: 510Pa
 Canadian Air Infiltration/Exfiltration: A3

Double Pane Glass ●
 Tri-pane Laminated Glass ●●
 Triple Pane Glass ●●●



THERMAL PERFORMANCE RATINGS

HC-101 CASEMENT