

GLAZING OPTIONS	STYLE	SHGC	U-VALUE	U-FACTOR	ER	VT	CANADA ENERGY STAR ZONE
Cl-Arg-180	●	0.50	0.26	1.47	36	0.57	1,2,3
Cl-Arg-180, Div under 1"	●	0.45	0.26	1.47	34	0.52	1,2,3
180-Arg-Cl	●	0.47	0.26	1.47	35	0.57	1,2,3
180-Arg-Cl, Div under 1"	●	0.43	0.26	1.47	32	0.52	1,2
180-Arg-i89	●	0.45	0.23	1.28	38	0.56	1,2,3
180-Arg-i89, Div under 1"	●	0.41	0.23	1.28	35	0.51	1,2,3
Lami-Arg-180	●●	0.45	0.26	1.48	33	0.56	1,2,3
Lami-Arg-180, Div under 1"	●●	0.41	0.26	1.48	31	0.51	1,2
180-Arg-Cl-Arg-180	●●●	0.41	0.20	1.12	39	0.50	1,2,3
180-Arg-Cl-Arg-180, Div under 1"	●●●	0.37	0.20	1.15	36	0.46	1,2,3
180-Arg-180 Arg-i89	●●●	0.39	0.18	1.02	40	0.49	1,2,3
180-Arg-180 Arg-i89, Div under 1"	●●●	0.35	0.18	1.04	37	0.45	1,2,3
180-Arg-180-Arg-i89, 1.375" OT	●●●	0.39	0.15	0.86	43	0.49	1,2,3
180-Arg-180-Arg-i89, 1.375" OT Div under 1"	●●●	0.35	0.15	0.86	41	0.45	1,2,3
180-Arg-Cl-Arg-180, 1.375" OT	●●●	0.41	0.16	0.93	43	0.50	1,2,3
180-Arg-Cl-Arg-180, 1.375" OT Div under 1"	●●●	0.37	0.16	0.93	41	0.46	1,2,3
180-ArgKry-Cl-ArgKry-180	●●●	0.41	0.18	1.00	42	0.50	1,2,3
180-ArgKry-Cl-ArgKry-180, Div under 1"	●●●	0.37	0.18	1.04	38	0.46	1,2,3
180-Kry-Cl-Kry-180	●●●	0.41	0.16	0.90	44	0.50	1,2,3
180-Kry-Cl-Kry-180, Div under 1"	●●●	0.37	0.17	0.94	40	0.46	1,2,3
272-Arg-Cl-Arg-272	●●●	0.26	0.19	1.09	31	0.41	1,2,3
272-Arg-Cl-Arg-272, Div under 1"	●●●	0.24	0.20	1.12	29	0.38	1,2,3
272-Arg-Cl-Arg-272, 1.375" OT	●●●	0.26	0.16	0.89	35	0.41	1,2,3
272-Arg-Cl-Arg-272, 1.375" OT, Div under 1"	●●●	0.24	0.16	0.89	34	0.38	1,2,3
272-ArgKry-Cl-ArgKry-272	●●●	0.26	0.17	0.97	34	0.41	1,2,3
272-ArgKry-Cl-ArgKry-272, Div under 1"	●●●	0.24	0.17	0.99	32	0.38	1,2,3
272-Kry-Cl-Kry-272	●●●	0.26	0.15	0.87	36	0.41	1,2,3
272-Kry-Cl-Kry-272, Div under 1"	●●●	0.24	0.16	0.89	34	0.38	1,2,3

Structural Ratings

AAMA/WDMA/CSA 101/1.S.2/A440-08 and A440S1-14
 Size Tested: 1220x 1015mm (48" x 40")
 R-PG55
 Positive Design Pressure = +2640 Pa (+55 psf)
 Negative Design Pressure = -2640 Pa (-55 psf)
 Water Test Pressure: 540Pa
 Canadian Air Infiltration/Exfiltration: A3

Double Pane Glass ●
 Tri-pane Laminated Glass ●●
 Triple Pane Glass ●●●



THERMAL PERFORMANCE RATINGS

HC-426 AWNING